



GLOBAL PILING EQUIPMENT INC.™

Distributed by: **Mississippi Valley Equipment Co.**
 1198 Pershall Rd. St. Louis, MO 63137
 (800)325-8001 www.mve-stl.com

Specifications: D 19-42 Diesel Pile Hammer

Dimensions approx:

Length of Hammer:	A1	5086 mm	16' 7" ft
Hammer length w/starter guides:	A	5586 mm	18' 3" ft
Outer diameter of impact block:	B	440 mm	1' 4" ft
Guiding Width:	C	660 mm	2' 2" ft
Width of hammer:	D	485 mm	1' 6" ft
Hammer Center to Pump Guard:	F	345 mm	1' 1" ft
Hammer Center to Trip:	G	280 mm	9" ft
Hammer Depth:	H	665 mm	2' 2" ft

VIEW PARTS MANUAL HERE

Pump Setting 1	50 %	29.2 kNm	21,510 ft.lbs.
Pump Setting 2	66 %	38.0 kNm	28,035 ft.lbs.
Pump Setting 3	83 %	47.8 kNm	35,260 ft.lbs.
Pump Setting 4	100 %	57.6 kNm	42,480 ft.lbs.

Weights approx:

Weight of diesel pile hammer approx.:	4.2 T	8400 lbs
Weight of piston approx.:	1820 kg	4012.4 lbs
Impact block approx.:	354 kg	780 lbs
Tripping device approx.:	160 kg	352.74 lbs
Tool box approx.:	75 kg	165.35 lbs

Energy per blow

Max:	57.5 kNm	42,410 ft lbf
Min:	29.1 kNm	21,463 ft lbf
Number of blows:		37-52 min

Batter Info

Max. gradient of batter pile driven:	1:3/1:1
--------------------------------------	---------

Consumption

Diesel fuel:	7.5 L hr.	1.98 gph
Lubrication oil:	.6 L hr.	.16 gph

Volume

Diesel oil tank:	71 L	18.8 gal
Lube tank:	20 L	5.3 gal

