



MKT HYDRAULIC AUGER SYSTEMS

- Fixed and variable torque models
- High output & torque speeds
- Remote pendant controls for all operations
- Lead mounted tie-back installation systems
- Pre-drilling, augercast, drilling out driven pipe
- Uncomplicated hydraulic circuitry
- Manufactured & assembled in St. Louis, MO
- Enclosed power units
- Custom auger systems



| AUGER | HA-18A | | HVA-40 | |
|----------------------|---------------|-----------|-------------------------|----------|
| Output Torque | 18,000 ft-lbs | | 14,000 to 40,000 ft-lbs | |
| Output Speed | 0-45 RPM | | 33 to 100 RPM | |
| Max. Line Pull/Crowd | 12 Tons | 106kN | 17 tons | 151kN |
| Lead Size | 8" x 20" | | 8" x 26" | |
| Length | 32 in. | 813 mm | 30 in. | 762 mm |
| Width | 20 ½ in. | 521 mm | 26 in. | 660 mm |
| Height | 66 in. | 1,676 mm | 60 in. | 1,592 mm |
| Weight | 2,250 lbs. | 1,023 kg. | 3,500 lbs. | 1,592 kg |
| Hose Bundle Length | 100 ft. | 30 m | 100 ft. | 30 m |
| POWER UNIT | | | | |
| Engine HP | 185 hp | 138 kW | 365 hp | 272 kW |
| Operating Speed | 2,400 RPM | | 2,250 RPM | |
| Hyd. Flow | 82 gpm | 310 lpm | 90 gpm | 342 lpm |
| Hyd. Pressure | 3,500 psi | 241 bar | 5,000 psi | 345 bar |
| Length | 120 in. | 3,048 mm | 132 in. | 3,353 mm |
| Width | 47 in. | 1,193 mm | 48 in. | 1,219 mm |
| Height | 66 in. | 1,676 mm | 84 in. | 2,134 mm |
| Weight | 5,750 lbs | 2,616 kg | 9,500 lbs | 4,322 kg |